
FlowStar DTM Specifications

- 1) Hood body constructed of extruded aluminum with clear anodized finish
- 2) Adjustable diffusion disc attached to inlet collar & adjustable through filter center divider
- 3) Galvanized hood sheet, hanging tabs, and Ducted Inlet (10" sized)
- 4) Filter constructed of extruded aluminum with clear anodized finish
- Media pack 2.0", 2.5", or 4.0" mini pleat with thermo plastic resin separators UL Rating: UL 900 Classified
- 6) Center divider with single access port
- 7) Protective expanded steel painted white screen on the filter air leaving side
- 8) Two component polyurethane pack to frame sealant
- 9) Minimum filter efficiency 99.99% at 0.3 micron and 100 fpm
- 10) Filters individually leak scan tested to maximum allowable leak rate of 0.01%
- 11) Filters manufactured in accordance with IEST-RP-CC001 Latest Revision
- 12) Filter tolerances are +0.00/-0.125 from listed dimensions
- 13) Filters will be square to within 1/8" for diagonals under 30 in. and Filters will be square to within 1/4" for diagonals over 30 in.

Filter & Air Resistance Information (Resistance based on open media face, 100 fpm air velocity)								
Item	DTM Size (W"xL"xH")	Filter Depth (Inches)	Pack Depth (Inches)	Max. Resistance (Inches W.G.)	Air Flow Rate (CFM)			
DTM-01 40645	23-5/8 x 23-5/8 x 7-7/8	5-7/8	2.5	0.45	320			
DTM-01 40646	23-5/8 x 47-5/8 x 7-7/8	5-7/8	2.5	0.45	690			
DTM-12 40628	23-5/8 x 23-5/8 x 7-1/4	5-1/4	2.0	0.52	320			
DTM-12 40630	23-5/8 x 47-5/8 x 7-1/4	5-1/4	2.0	0.52	690			
DTM-20 41774	23-5/8 x 23-5/8 x 9-1/4	7-1/4	4.0	0.36	320			
DTM-20 41776	23-5/8 x 47-5/8 x 9-1/4	7-1/4	4.0	0.36	690			



W L

Section View

		SP	ECIFICATION	N INFORMATION	
Custo	mer Inform	nation:			
	li imala a vi				
Item iv	lumber:				
	For N	on-Star	ndard Sizes, F	Please Consult the Factory.	
		(H)	X	(W) X	(D)
	Ple	ease Spe	cify Size as Nom	inal or Exact	<u> </u>
			SPECIFIED	O OPTIONS	
	·				
	Customer In	itial and [Date for Product	Specification	
			C	FLOWS	T/IR
	0 0 0 0 0	Indoor	Air Quality		W
	FLO	ows.	TAR DTM	l - 10" Inlet Collar	
Rev	ВС	Date:	4/12/2018	Drawing Number:	Revision:
	Filtration@	rouplA	O com	SD-DTM 10in	06